



## Ovenworx™ H1 Syn Chain Lubricant (4061)

*Superior Heat Resistance Keeps Oven Chain Operating Freely*

.....

Ovenworx™ H1 Syn Chain Lubricant (4061) was formulated specifically to combat the demanding conditions present with oven chain applications. In addition, it is approved for incidental food contact and contains no artificial dyes, making it a good choice for food manufacturing plants.

Oven chain efficiency is dependent upon a lubricant that can keep the chain operating freely and smoothly, fighting the ever present heat and moisture that can cause corrosion and eventually lead to premature failure of oven chain pins and bushings. Only the most robust lubricant formulations can perform in this application; it is not an area to cut corners. If the oven chain fails, output comes to a screeching halt.

In addition to this high level of protection, equipment runs more cleanly and efficiently with Ovenworx 4061, which lubricates without the need of solids. Lubricants with solids have to be stirred to keep the solids distributed within the carrier and prevent them from falling out of the suspension. Solids also can create housekeeping issues by building up over time, creating gum and gunk around the application area, especially when over-applied.



### Beneficial Qualities

#### High-Performance

- Fully synthetic formula features robust high-viscosity base fluid
- Penetrates all moving parts of the oven chain, enabling them to move freely
- Ensures quiet, smooth operation
- Decreases energy consumption by reducing frictional drag on electric motors
- Seals out equipment-damaging moisture, preventing corrosion

#### Resists High Temperatures

- Lubricates chains up to 300°C (572°F)
- Features oxidation stability and reduced volatility at high temperatures

- Has broad temperature range and high flash point
- Contains no solid additives to fall out of suspension

#### Easy To Apply & Use

- Contains no solids; requires no pre-mixing
- Can be applied to hot oven chains without interrupting operation
- Leaves no residue; will not create cleanup issues

#### Approved for Food Manufacturing

- Contains no artificial dyes; is low-staining and odor neutral
- Meets NSF H1
- Certified Halal by IFANCA
- Certified Kosher Pareve



## Ovenworx™ H1 Syn Chain Lubricant

### Performance Requirements Met or Exceeded

- Halal (certified by IFANCA)
- Kosher Pareve
- NSF H1

### Industry Recommendations

- Industrial process ovens
- Food processing ovens

### Typical Applications

- Automatic lubrication systems for baking ovens
- Kiln chain drives
- Skate chains in bread and bun baking ovens
- Stenter & tenter chains
- Other high-temperature oven chains

	<b>4061</b>
<b>Color</b>	Clear
<b>ISO VG</b>	220
<b>Relative Density @ 60°F/60°F, ASTM D1298</b>	0.976
<b>Viscosity @ 100°C, cSt, ASTM D445</b>	19.24
<b>Viscosity @ 40°C, cSt, ASTM D445</b>	224.1
<b>Viscosity Index ASTM D2270</b>	96
<b>Flash Point °C (°F), (COC), ASTM D92</b>	300 (572)
<b>Pour Point °C (°F), ASTM D97</b>	-39 (-38)
<b>Four-Ball Wear @ 75°C, 1,200 rpm, 40 kgf, 60 minutes, mm wear, ASTM D4172</b>	0.32
<b>SRV Wear 50°C, 1 mm stroke, 50 Hz frequency, ball on disc, break-in load 50 N, test load 300 N, 2 hrs, ASTM D6425</b>	
<b>Wear Scars on Ball Length, mm</b>	0.80
<b>Wear Scars on Ball Width, mm</b>	0.80
<b>Coefficient of Friction Minimum</b>	0.115
<b>Coefficient of Friction Maximum</b>	0.135



Ovenworx™ is a trademark of Lubrication Engineers, Inc.

LI30119 1-14, rev. 2-15