# VIPER MINI MK 3 WIRE ROPE LUBRICATOR

#### IMPROVED ROPE CAPACITY 6MM TO 44MM

## Safe, fast, efficient and environmentally responsible solution for lubricating wire ropes

The Viper<sup>®</sup> Mini MK 3 Wire Rope Lubricator is designed to enable lubricant to migrate into the rope ensuring total coverage of lubricant. The Collar is manufactured from high strength aluminium alloy with a robust coating to maximise corrosion resistance in harsh environments. Designed for wire rope lubrication of mobile cranes, tower cranes, deck winches, construction and service cranes, anchor ropes and small marine cranes.





- Increases the life of wire rope assets by up to 300%
- Increases the time between relubrication
- Provides a safer, cleaner work environment
- 🖊 Made in Australia

#### HOW VIPER® MINI MK 3 INCREASES SITE EFFICIENCIES & REDUCES COST

Compact & Lightweight	Only 3.5kg making the Viper <sup>®</sup> Mini MK 3 ideal for single person operation
	Minimises WHS issues whilst working at heights
Cost Effective	Preventative regulated maintenance increases asset longevity
	Lubricates ropes up to 2000 metres per hour
	Reduces relubrication times from several days to just hours reducing manual labour by up to 90%
	<ul> <li>Specially designed seal provides durability in harsh environments whilst ejecting moisture and water maximising corrosion resistance</li> </ul>

www.viperwrl.com

# HEALTH SAFETY ENVIRONMENT BENEFITS

The most environmentally responsible method for cleaning and lubricating wire ropes.

### **VIPER MINI MK 3 KIT INCLUSIONS**

- VIPER MINI MK 3 COLLAR, HIGH PRESSURE PUMP 50:1; 2,900 GRAMS/MIN
- COMPLETE WITH AIR-REGULATOR AND AIR ISOLATION VALVE TO ENABLE SAFER OPERATION
- GREASE PUMP COMPLETE WITH DRUM COVER, CARRY HANDLE, FOLLOWER PLATE AND 4M HOSE WITH QUICK CONNECTS AT EACH END
- RETAINING RATCHET STRAPS & SHACKLES
- ROBUST CORROSION RESISTANT ALUMINIUM STORAGE CASE

- Every gram of lubricant is used on the rope with no leakage eliminating waste and environment impact
- No direct contact with the lubricant and avoids risk of accidental spillage
  - The rope can be lubricated from a safe distance reducing hazardous safety risks
  - At 3.5kg it allows for safe single person application



\*Note Seals are sold separately

Identification plate for asset management

Corrosion resistant Collar

Increased dimensions of locking mechanism for maximum clamping force

New wider hinge mouth design provides greater strength for maximum wire rope capacity

Durable dual handle design for controlled tightening

INDUSTRIES MARINE

- MINING
- **CONSTRUCTION**
- **SHIPPING**
- OIL & GAS
- DEFENCE FORCE

providing greater clearance for cleaner to operate effectively

Enlarged ratchet

strapping points

WIRE ROPE LUBRICATOR

Optional dual lubrication point for high-speed applications

Lubrication point

Distributed by:

LEARN MORE

sales@viperwrl.com 26 Prince William Drive, Seven Hills, NSW, Australia 2147

Phone +61 2 9636 5655 www.viperwrl.com

The information and contents of this brochure are the copyright of the publisher. Whilst all care has been taken in the production of this brochure we assume no responsibility for errors or om and no liability can be accepted for any loss or damage direct, indirect or consequential arising from the use of information contained in this brochure. Copyright Lubrication Engineering Pty Ltd (06/2023)